

ROBOT CABLES

Temperature (°C) - flexing

Temperature (°C) - fixed

Nominal voltage U₀/U

Bending radius - flexing x Ø

Bending radius - fixed x Ø

Halogen-free

UV-resistant

Outdoor use

Drag chain

Colored cores/VDE 0293

Screened/shielded

HAR/VDE REG no./VDE
UL/CSA

Page

Robot cables														
	Temperature (°C) - flexing	Temperature (°C) - fixed	Nominal voltage U ₀ /U	Bending radius - flexing x Ø	Bending radius - fixed x Ø	Halogen-free	UV-resistant	Outdoor use	Drag chain	Colored cores/VDE 0293	Screened/shielded	HAR/VDE REG no./VDE	UL/CSA	Page
ROBOFLEX® recycle	-30 to +105	-40 to +105	300	7.5x	7.5x	X	X	X		X				262
ROBOFLEX® 2001 / 2001-C	-30 to +80	-40 to +80	300/500	7.5x	7.5x		X	X			/X			264
ROBOFLEX® 150,...151,...152,...153	-40 to +80	-40 to +80	300/500	15x	15x	X	X	X		/X	X			265
ROBOFLEX® sewer robot	-40 to +80	-40 to +80	300/500				X	X						267

The selection table is intended as an initial orientation.
Please see the relevant page of the catalogue for detailed information on the product properties.

