

■ TRAILING CABLES

Temperature (°C) - flexing

Temperature (°C) - fixed

Nominal voltage U₀/U

Bending radius - flexing x Ø

Bending radius - fixed x Ø

Halogen-free

UV-resistant

Outdoor use

Drag Chain

Colored cores/VDE 0293

Screened/shielded

HAR/VDE REG no./VDE
UL/CSA

Page

Trailing Cables														
	Temperature (°C) - flexing	Temperature (°C) - fixed	Nominal voltage U ₀ /U	Bending radius - flexing x Ø	Bending radius - fixed x Ø	Halogen-free	UV-resistant	Outdoor use	Drag Chain	Colored cores/VDE 0293	Screened/shielded	HAR/VDE REG no./VDE	UL/CSA	Page
TROMMPUR®	-40 bis +80	-40 to +80	300/500	10x	10x	X	X	X		X				254
Flugzeugheber-T	-20 to +80	-20 to +80	300/500	15x	15x			X	X					255
NSHTÖU	-35 to +70	-40 to +70	0.6/1 kV	7.5x	7.5x			X	X	X		X		256
(N)SHTÖU-V	-25 to +80	-25 to +80	0.6/1 kV	7.5x	7.5x			X		X				257
(N)TSCGEWÖU	-20 to +60	-20 to +80	6-20 kV	15x	15x			X	X					258

The selection table is intended as an initial orientation.
Please see the relevant page of the catalogue for detailed information on the product properties.

