

DATA & COMPUTER CABLES

Temperature (°C) - flexing
 Temperature (°C) - fixed
 Nominal voltage U₀/U
 Operating top level voltage
 Bending radius - flexing x Ø
 Bending radius - fixed x Ø
 Halogen-free
 UV-resistant
 Outdoor use
 Drag chain
 Colored cores/VDE 0293
 Screened/shielded
 HAR/VDE REG no./VDE
 UL/CSA
Page

Data & computer cables													
TRONIC (LiYY)	-5 to +80	-40 to +80	350	7.5x	4x						X	124	
PAAR-TRONIC	-5 to +80	-30 to +80	350	7.5x	4x						X	126	
SENSORFLEX®	-5 to +80	-30 to +80	350	7.5/15x						(X)	X	128	
VERTEILERFLEX	-5 to +80	-30 to +80	300/500	7.5/15x						(X)	X	129	
DATAFLAMM®	+5 to +70	-40 to +70	350	7.5x	7.5x	X					X	130	
TRONIC-CY (LiY-CY)	-5 to +80	-40 to +80	350	10x	5x						X	X	131
PAAR-TRONIC-CY	-5 to +80	-30 to +80	350	10x	5x						X	X	133
PAAR-CY-OZ	-5 to +80	-40 to +80	300/500	10x	5x							X	135
PAAR-TRONIC-CY-CY (LiYCY-CY)	-5 to +80	-40 to +80	350	12x	6x						X	X	136
PAAR-TRONIC-Li-2YCV	-5 to +70	-30 to +80	250	12x	7.5x			X			X	X	138
PAAR-TRONIC-Li-2YCY	-5 to +70	-30 to +80	250	12x	7.5x						X	X	139
LiYCY	-5 to +70	-40 to +70	350	10x	5x						X	X	140
TRONIC 1-CY	-5 to +80	-40 to +80	250	10x	5x						X	X	141
TRONIC 2-CY	-5 to +80	-40 to +80	350	10x	5x						X	X	142
LiY-TPC-Y	-5 to +70	-30 to +70	500	12x	7.5x						X	X	143
DATAPUR®-C	-5 to +80	-40 to +80	350	10x	5x		X	X			X	X	144
DATAFLAMM®-C	+5 to +70	-40 to +70	350	7.5x	7.5x	X					X	X	145
DATAFLAMM®-C-PAAR	+5 to +70	-40 to +70	350	7.5x	7.5x	X					X	X	146
EDV-PIMF-CY	-5 to +80	-20 to +80	300	10x	5x						X	X	147
RD-Y(St)Y	-5 to +50	-40 to +70	600	7.5x	7.5x						X	X	148
RD-Y(St)Yv / RD-Y(St)YY	-5 to +50	-40 to +70	600	7.5x	7.5x			X			X	X	149
RE-2Y(St)YV	-5 to +50	-40 to +70	300	7.5x	7.5x			X			X	X	150
RE-2Y(St)YV PIMF	-5 to +50	-40 to +70	300	7.5x	7.5x			X			X	X	151
JE-Y(St)Y	-5 to +50	-30 to +70	225		6x						X	X	152
JE-LiYCY	-5 to +50	-30 to +70	225		6x						X	X	153
JE-LiHCH	-5 to +50	-30 to +70	225	7.5x	7.5x	X					X	X	154
RD-H(St)H	-5 to +50	-30 to +70	225	7.5x	7.5x	X		(X)			X	X	155

The selection table is intended as an initial orientation.
 Please see the relevant page of the catalogue for detailed information on the product properties.

