

■ ALLWEATHER & RUBBER CABLES

Temperature (°C) - flexing

Temperature (°C) - fixed

Nominal voltage U₀/U

Bending radius - flexing x Ø

Bending radius - fixed x Ø

Halogen-free

UV-resistant

Outdoor use

Drag Chain

Colored cores/VDE 0293

Screened/shielded

HAR/VDE REG no./VDE
UL/CSA

Page

Allweather & rubber cables													
	Temperature (°C) - flexing	Temperature (°C) - fixed	Nominal voltage U ₀ /U	Bending radius - flexing x Ø	Bending radius - fixed x Ø	Halogen-free	UV-resistant	Outdoor use	Drag Chain	Colored cores/VDE 0293	Screened/shielded	HAR/VDE REG no./VDE UL/CSA	Page
YELLOWFLEX	-25 to +60	-30 to +60	450/750	7.5x	4x			X	X				240
H05RR-F / H05RN-F		-30 to +60	300/500	7.5x	7.5x			(X)	X		X		241
H07RN-F		-30 to +60	450/750	7.5x	4x			X	X		X		242
A07RN-F		-30 to +60	450/750	7.5x	4x			X	X		X		244
NEOPRENE control cable	-25 to +60	-40 to +80	300/500	12.5x	12.5x			X	X				245
NSSHÖU	-25 to +80	-40 to +80	0.6/1 kV	10x	4x			X	X		X		246
LIFT-TRAGO®-30 / -60	-5 to +50	-40 to +70	300/500	20x	20x								247
TRAGO / Lift-2S	-15 to +70	-40 to +70	300/500	20x	20x	X	X		X				248
BAULIFTKABEL B101 / B102 / B103	-10 to +80	-10 to +80	300/500	10x	10x	X	X						249
HELUSPREADER YSLTÖ-J	-20 to +60	-20 to +60	300/500	15x	15x	X	X						250

The selection table is intended as an initial orientation.
Please see the relevant page of the catalogue for detailed information on the product properties.

F