


Fibre Optic Outdoor Cable

acc. DIN VDE 0888

HELUCOM®

A-DF(ZN)2Y



Cable structure

Core type: Loose tube
 GRP support element
 Strain relief elements: Aramide
 Outer sheath material: PE
 Outer sheath colour: Black

Temperature range

Laying, min.: -5°C
 Laying, max.: +50°C
 Operating, min.: -20°C
 Operating, max.: +60°C

Other data

Corrosiveness acc. to EN50267-2-3
 Halogen-free acc. to 60754-2
 Longitudinally water-tight acc. to IEC 60794-1-2-F5
 UV-resistant

Designation	No. of fibres	Fibre type	Fibre category	Number of fibres per core	Outer Ø app. mm	Max. tensile force N	Min. stat. bending radius mm	Caloric load app. MJ / m	Max. transverse pressure N / cm	Weight kg / km	Part no.
A-DF(ZN)2Y	2	Multimode G50/125	OM2	2	9,5	2500	95,0	4,20	400	85,0	80016
A-DF(ZN)2Y	2	Multimode G62.5/125	OM1	2	9,5	2500	95,0	4,20	400	85,0	80033
A-DF(ZN)2Y	2	Single-mode E9/125	ITU-T G.652	2	9,5	2500	95,0	4,20	400	85,0	80000
A-DF(ZN)2Y	4	Multimode G50/125	OM2	4	9,5	2500	95,0	4,20	400	85,0	80017
A-DF(ZN)2Y	4	Multimode G62.5/125	OM1	4	9,5	2500	95,0	4,20	400	85,0	80034
A-DF(ZN)2Y	4	Single-mode E9/125	ITU-T G.652	4	9,5	2500	95,0	4,20	400	85,0	80001
A-DF(ZN)2Y	8	Multimode G50/125	OM2	8	9,5	2500	95,0	4,20	400	85,0	80019
A-DF(ZN)2Y	8	Multimode G62.5/125	OM1	8	9,5	2500	95,0	4,20	400	85,0	80036
A-DF(ZN)2Y	8	Single-mode E9/125	ITU-T G.652	8	9,5	2500	95,0	4,20	400	85,0	80003
A-DF(ZN)2Y	12	Multimode G50/125	OM2	12	9,5	2500	95,0	4,20	400	85,0	80021
A-DF(ZN)2Y	12	Multimode G62.5/125	OM1	12	9,5	2500	95,0	4,20	400	85,0	80038
A-DF(ZN)2Y	12	Single-mode E9/125	ITU-T G.652	12	9,5	2500	95,0	4,20	400	85,0	80005
A-DF(ZN)2Y	24	Multimode G50/125	OM2	12	9,5	2700	95,0	4,00	400	85,0	80024
A-DF(ZN)2Y	24	Multimode G62.5/125	OM1	12	9,5	2700	95,0	4,00	400	85,0	80041
A-DF(ZN)2Y	24	Single-mode E9/125	ITU-T G.652	12	9,5	2700	95,0	4,00	400	85,0	80008
A-DF(ZN)2Y	36	Multimode G50/125	OM2	12	9,5	2700	95,0	4,00	400	85,0	80912
A-DF(ZN)2Y	36	Multimode G62.5/125	OM1	12	9,5	2700	95,0	4,00	400	85,0	80913
A-DF(ZN)2Y	36	Single-mode E9/125	ITU-T G.652	12	9,5	2700	95,0	4,00	400	85,0	80914
A-DF(ZN)2Y	48	Multimode G50/125	OM2	12	9,5	2700	95,0	4,00	400	85,0	80026
A-DF(ZN)2Y	48	Multimode G62.5/125	OM1	12	9,5	2700	95,0	4,00	400	85,0	80046
A-DF(ZN)2Y	48	Single-mode E9/125	ITU-T G.652	12	9,5	2700	95,0	4,00	400	85,0	80010
A-DF(ZN)2Y	60	Multimode G50/125	OM2	12	9,5	2700	95,0	4,00	400	85,0	80027
A-DF(ZN)2Y	60	Multimode G62.5/125	OM1	12	9,5	2700	95,0	4,00	400	85,0	80047
A-DF(ZN)2Y	60	Single-mode E9/125	ITU-T G.652	12	9,5	2700	95,0	4,00	400	85,0	80011
A-DF(ZN)2Y	72	Multimode G50/125	OM2	12	10,0	2700	100,0	3,80	400	90,0	80473
A-DF(ZN)2Y	72	Multimode G62.5/125	OM1	12	10,0	2700	100,0	3,80	400	90,0	80474
A-DF(ZN)2Y	72	Single-mode E9/125	ITU-T G.652	12	10,0	2700	100,0	3,80	400	90,0	80475
A-DF(ZN)2Y	84	Multimode G50/125	OM2	12	10,7	3000	107,0	4,30	400	120,0	80028
A-DF(ZN)2Y	84	Multimode G62.5/125	OM1	12	10,7	3000	107,0	4,30	400	120,0	80048
A-DF(ZN)2Y	84	Single-mode E9/125	ITU-T G.652	12	10,7	3000	107,0	4,30	400	120,0	80012
A-DF(ZN)2Y	96	Multimode G50/125	OM2	12	11,5	3000	115,0	5,00	400	135,0	80777
A-DF(ZN)2Y	96	Multimode G62.5/125	OM1	12	11,5	3000	115,0	5,00	400	135,0	80774
A-DF(ZN)2Y	96	Single-mode E9/125	ITU-T G.652	12	11,5	3000	115,0	5,00	400	135,0	80764
A-DF(ZN)2Y	144	Multimode G50/125	OM2	12	14,5	3000	145,0	7,70	400	175,0	80032
A-DF(ZN)2Y	144	Multimode G62.5/125	OM1	12	14,5	3000	145,0	7,70	400	175,0	80051
A-DF(ZN)2Y	144	Single-mode E9/125	ITU-T G.652	12	14,5	3000	145,0	7,70	400	175,0	80015

Dimensions and specifications may be changed without prior notice.

Application

These HELUCOM® fibre-optic cables are characterized by a stranded construction with jelly filling. They are made waterproof in longitudinal direction by filling a jelly mass into the stranding cavities. Non-metallic tension elements ensure above average strain relief. This construction is particularly used in the area of telecommunication and long distance, but also in regular channels and tubes.

Fibre Optic Outdoor Cable

acc. DIN VDE 0888

HELUCOM®

A-DF(ZN)B2Y



Cable structure

Core type: Loose tube
GRP support element
Strain relief elements: Aramide
Type of armouring: Glass yarns
Outer sheath material: PE
Outer sheath colour: Black

Temperature range

Laying, min.: -5°C
Laying, max.: +50°C
Operating, min.: -20°C
Operating, max.: +60°C

Other data

Corrosiveness acc. to EN50267-2-3
Halogen-free acc. to 60754-2
Longitudinally water-tight acc. to IEC 60794-1-2-F5
UV-resistant

Designation	No. of fibres	Fibre type	Fibre category	Number of fibres per core	Outer Ø app. mm	Max. tensile force N	Min. stat. bending radius mm	Caloric load app. MJ / m	Max. transverse pressure N / cm	Weight kg / km	Part no.
A-DF(ZN)B2Y	2	Multimode G50/125	OM2	2	10,5	2700	105,0	4,40	400	90,0	80100
A-DF(ZN)B2Y	2	Multimode G62.5/125	OM1	2	10,5	2700	105,0	4,40	400	90,0	80115
A-DF(ZN)B2Y	2	Single-mode E9/125	ITU-T G.652	2	10,5	2700	105,0	4,40	400	90,0	80084
A-DF(ZN)B2Y	4	Multimode G50/125	OM2	4	10,5	2700	105,0	4,40	400	90,0	80101
A-DF(ZN)B2Y	4	Multimode G62.5/125	OM1	4	10,5	2700	105,0	4,40	400	90,0	80116
A-DF(ZN)B2Y	4	Single-mode E9/125	ITU-T G.652	4	10,5	2700	105,0	4,40	400	90,0	80085
A-DF(ZN)B2Y	8	Multimode G50/125	OM2	8	10,5	2700	105,0	4,40	400	90,0	80031
A-DF(ZN)B2Y	8	Multimode G62.5/125	OM1	8	10,5	2700	105,0	4,40	400	90,0	80771
A-DF(ZN)B2Y	8	Single-mode E9/125	ITU-T G.652	8	10,5	2700	105,0	4,40	400	90,0	80087
A-DF(ZN)B2Y	12	Multimode G50/125	OM2	12	10,5	2700	105,0	4,40	400	90,0	80104
A-DF(ZN)B2Y	12	Multimode G62.5/125	OM1	12	10,5	2700	105,0	4,40	400	90,0	80120
A-DF(ZN)B2Y	12	Single-mode E9/125	ITU-T G.652	12	10,5	2700	105,0	4,40	400	90,0	80089
A-DF(ZN)B2Y	24	Multimode G50/125	OM2	12	10,5	2700	105,0	4,40	400	90,0	80759
A-DF(ZN)B2Y	24	Multimode G62.5/125	OM1	12	10,5	2700	105,0	4,40	400	90,0	80123
A-DF(ZN)B2Y	24	Single-mode E9/125	ITU-T G.652	12	10,5	2700	105,0	4,40	400	90,0	80092
A-DF(ZN)B2Y	36	Multimode G50/125	OM2	12	10,5	2700	105,0	4,30	400	90,0	81137
A-DF(ZN)B2Y	36	Multimode G62.5/125	OM1	12	10,5	2700	105,0	4,30	400	90,0	81138
A-DF(ZN)B2Y	36	Single-mode E9/125	ITU-T G.652	12	10,5	2700	105,0	4,30	400	90,0	81139
A-DF(ZN)B2Y	48	Multimode G50/125	OM2	12	10,5	2700	105,0	4,20	400	90,0	80109
A-DF(ZN)B2Y	48	Multimode G62.5/125	OM1	12	10,5	2700	105,0	4,20	400	90,0	80125
A-DF(ZN)B2Y	48	Single-mode E9/125	ITU-T G.652	12	10,5	2700	105,0	4,20	400	90,0	80094
A-DF(ZN)B2Y	60	Multimode G50/125	OM2	12	10,5	2700	105,0	4,20	400	90,0	80110
A-DF(ZN)B2Y	60	Multimode G62.5/125	OM1	12	10,5	2700	105,0	4,20	400	90,0	80126
A-DF(ZN)B2Y	60	Single-mode E9/125	ITU-T G.652	12	10,5	2700	105,0	4,20	400	90,0	80095
A-DF(ZN)B2Y	72	Multimode G50/125	OM2	12	11,0	2700	110,0	4,10	400	95,0	81143
A-DF(ZN)B2Y	72	Multimode G62.5/125	OM1	12	11,0	2700	110,0	4,10	400	95,0	81144
A-DF(ZN)B2Y	72	Single-mode E9/125	ITU-T G.652	12	11,0	2700	110,0	4,10	400	95,0	81145
A-DF(ZN)B2Y	84	Multimode G50/125	OM2	12	11,5	3000	115,0	4,60	400	136,0	80111
A-DF(ZN)B2Y	84	Multimode G62.5/125	OM1	12	11,5	3000	115,0	4,60	400	136,0	80127
A-DF(ZN)B2Y	84	Single-mode E9/125	ITU-T G.652	12	11,5	3000	115,0	4,60	400	136,0	80096
A-DF(ZN)B2Y	96	Multimode G50/125	OM2	12	12,0	3000	120,0	5,30	400	155,0	81147
A-DF(ZN)B2Y	96	Multimode G62.5/125	OM1	12	12,0	3000	120,0	5,30	400	155,0	81148
A-DF(ZN)B2Y	96	Single-mode E9/125	ITU-T G.652	12	12,0	3000	120,0	5,30	400	155,0	81149
A-DF(ZN)B2Y	144	Multimode G50/125	OM2	12	14,5	3000	145,0	8,00	400	228,0	80114
A-DF(ZN)B2Y	144	Multimode G62.5/125	OM1	12	14,5	3000	145,0	8,00	400	228,0	80130
A-DF(ZN)B2Y	144	Single-mode E9/125	ITU-T G.652	12	14,5	3000	145,0	8,00	400	228,0	80099

Dimensions and specifications may be changed without prior notice.

Application

These HELUCOM® fibre-optic cables are characterized by a stranded construction with jelly filling. They are made waterproof in longitudinal direction by filling a jelly mass into the stranding cavities. Non-metallic tension elements and glass yarns ensure above average strain relief and rodent protection. This construction is particularly used in the area of telecommunication and long distance, but also in regular channels and tubes where rodent infestation is possible.