

**H07ZZ-F** control cable, cross linked, halogen-free**Technical data**

- halogen-free cross-linked control cable to DIN VDE 0285-525-3-21 / DIN EN 50525-3-21
- **Temperature range**  
flexing -5°C to +70°C  
fixed installation -20°C to +70°C
- Permissible **operating temperature** at conductor +90°C
- **Nominal voltage**  
flexing  $U_0/U$  450/750 V  
fixed installation  $U_0/U$  0,6/1 kV
- **Test voltage** 2500 V
- **Permanent tensile load**  
max. 15 N/mm<sup>2</sup>  
under consideration of total copper cross-sections
- **Minimum bending radius**  
flexing 10x cable Ø  
for fixed installation 4x cable Ø

**Cable structure**

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5, HD 383
- Core insulation of halogen-free, cross-linked EI8 to DIN VDE 0207-363-5/DIN EN 50363-5
- Core identification to DIN VDE 0293-308
- Cores stranded in layers with optimal lay-length
- Outer sheath of halogen-free, cross-linked EM8 to DIN VDE 0207-363-6/DIN EN 50363-6
- Sheath colour black

**Properties****Test****Behaviour in fire**

- to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1 and IEC 60332-3-24
- Corrosiveness of combustion gases acc. to EN 50267-2-2
- Smoke density to DIN VDE 0482 part 1034-1+2, DIN EN 61034-1+2, IEC 61034-1+2
- **Ozone resistant** of single core the insulation to DIN VDE 0473-811-403 / DIN EN 60811-403

**Note**

- G = with green-yellow conductor  
x = without green-yellow conductor
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.

**Application**

Single and multicore sheathed cable, with low smoke and corrosive gas production in case of fire for interior use. Not suitable for continuous outside use. In this case, cable with a special tested covering should be used. Skin contact should be avoided when the cable is used in high temperatures.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø min. - max. approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
37176	1 x 1,5	5,7 - 7,1	14,4	58,0	16
37177	1 x 2,5	6,3 - 7,9	24,0	71,0	14
37178	1 x 4	7,2 - 9,0	38,0	100,0	12
37179	1 x 6	7,9 - 9,8	58,0	130,0	10
37180	1 x 10	9,5 - 11,9	96,0	230,0	8
37181	1 x 16	10,8 - 13,4	154,0	290,0	6
37182	1 x 25	12,7 - 15,8	240,0	420,0	4
37183	1 x 35	14,3 - 17,9	336,0	530,0	2
37184	1 x 50	16,5 - 20,6	480,0	750,0	1
37185	1 x 70	18,6 - 23,3	672,0	960,0	2/0
37186	1 x 95	20,8 - 26,0	912,0	1250,0	3/0
37187	1 x 120	22,8 - 28,6	1152,0	1560,0	4/0
37188	1 x 150	25,2 - 31,4	1440,0	1900,0	300 kcmil
37189	1 x 185	27,6 - 34,4	1776,0	2300,0	350 kcmil
37190	1 x 240	30,6 - 38,3	2304,0	2950,0	500 kcmil
37191	1 x 300	33,5 - 41,9	2880,0	3600,0	600 kcmil
37192	1 x 400	37,4 - 46,8	3840,0	4600,0	750 kcmil
37193	1 x 500	41,3 - 52,0	4800,0	6000,0	1000 kcmil
37194	2 x 1	7,7 - 10,0	19,0	95,0	18
37195	2 x 1,5	8,5 - 11,0	29,0	119,0	16
37196	2 x 2,5	10,2 - 13,1	48,0	172,0	14
37197	2 x 4	11,8 - 15,1	77,0	239,0	12
37198	2 x 6	13,1 - 16,8	115,0	319,0	10
37199	2 x 10	17,7 - 22,6	192,0	572,0	8
37200	2 x 16	20,2 - 25,7	307,0	767,0	6
37201	2 x 25	24,3 - 30,7	480,0	1154,0	4
37202	3 G 1	8,3 - 10,7	29,0	115,0	18
37203	3 G 1,5	9,2 - 11,9	43,0	144,0	16
37204	3 G 2,5	10,9 - 14,0	72,0	211,0	14
37205	3 G 4	12,7 - 16,2	115,0	290,0	12
37206	3 G 6	14,1 - 18,0	173,0	391,0	10
37207	3 G 10	19,1 - 24,2	288,0	706,0	8
37208	3 G 16	21,8 - 27,6	461,0	961,0	6
37209	3 G 25	26,1 - 33,0	720,0	1438,0	4
37210	3 G 35	29,3 - 37,1	1008,0	1814,0	2
37211	3 G 50	34,1 - 42,9	1440,0	2550,0	1
37212	3 G 70	38,4 - 48,3	2016,0	3210,0	2/0
37213	3 G 95	43,3 - 54,0	2736,0	4423,0	3/0
37214	3 G 120	47,4 - 60,0	3456,0	5405,0	4/0
37215	3 G 150	52,0 - 66,0	4320,0	6725,0	300 kcmil
37216	3 G 185	57,0 - 72,0	5328,0	8222,0	350 kcmil
37217	3 G 240	65,0 - 82,0	6192,0	10224,0	500 kcmil

Part no.	No. cores x cross-sec. mm <sup>2</sup>	Outer Ø min. - max. approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
37218	3 G 300	72,0 - 90,0	8640,0	12620,0	600 kcmil
37219	4 G 1	9,2 - 11,9	38,0	141,0	18
37220	4 G 1,5	10,2 - 13,1	58,0	176,0	16
37221	4 G 2,5	12,1 - 15,5	96,0	235,0	14
37222	4 G 4	14,0 - 17,9	154,0	365,0	12
37223	4 G 6	15,7 - 20,0	230,0	501,0	10
37224	4 G 10	20,9 - 26,5	384,0	872,0	8
37225	4 G 16	23,8 - 30,1	614,0	1194,0	6
37226	4 G 25	28,9 - 36,6	960,0	1822,0	4
37227	4 G 35	32,5 - 41,1	1344,0	2307,0	2
37228	4 G 50	37,7 - 47,5	1920,0	3253,0	1
37229	4 G 70	42,7 - 54,0	2688,0	4130,0	2/0
37230	4 G 95	48,4 - 61,0	3648,0	5720,0	3/0
37231	4 G 120	53,0 - 66,0	4608,0	6965,0	4/0
37232	4 G 150	58,0 - 73,0	5760,0	8644,0	300 kcmil
37233	4 G 185	64,0 - 80,0	7104,0	10598,0	350 kcmil
37234	4 G 240	72,0 - 91,0	9216,0	12100,0	500 kcmil
37235	4 G 300	80,0 - 101,0	11520,0	15200,0	600 kcmil
37236	5 G 1	10,2 - 13,1	48,0	170,0	18
37237	5 G 1,5	11,2 - 14,4	72,0	214,0	16
37238	5 G 2,5	13,3 - 17,0	120,0	316,0	14
37239	5 G 4	15,6 - 19,9	192,0	448,0	12
37240	5 G 6	17,5 - 22,2	288,0	607,0	10
37241	5 G 10	22,9 - 29,1	480,0	1075,0	8
37242	5 G 16	26,4 - 33,3	768,0	1480,0	6
37243	5 G 25	32,0 - 40,4	1200,0	2255,0	4
37244	6 G 1,5	13,4 - 17,2	84,0	287,0	16
37245	6 G 2,5	15,7 - 20,0	144,0	420,0	14
37246	6 G 4	18,2 - 23,2	230,0	583,0	12
37247	7 G 1,5	11,4 - 14,4	101,0	303,0	16
37248	7 G 2,5	13,4 - 17,0	168,0	448,0	14
37249	12 G 1,5	17,6 - 22,4	173,0	496,0	16
37250	12 G 2,5	20,6 - 26,2	288,0	724,0	14
37251	12 G 4	24,4 - 30,9	461,0	1042,0	12
37252	18 G 1,5	20,7 - 26,3	259,0	702,0	16
37253	18 G 2,5	24,4 - 30,9	432,0	1045,0	14
37254	18 G 4	28,8 - 36,4	691,0	1430,0	12
37255	24 G 1,5	24,3 - 30,7	346,0	935,0	16
37256	24 G 2,5	28,8 - 36,4	576,0	1325,0	14
37257	36 G 1,5	27,8 - 35,2	518,0	1297,0	16
37258	36 G 2,5	33,2 - 41,8	864,0	1949,0	14

Dimensions and specifications may be changed without prior notice. (RF01)