

# BIOFLEX-500®-JZ-C Bio-fuel resistant, abrasion resistant, recyclable environment friendly, bio-oil resistant<sup>1)</sup>, Cu-screened, EMC-preferred type, meter marking



## Technical data

- Bio-oil resistant, abrasion resistant special control cable in adapted to DIN VDE 0285-525-1 / DIN EN 50525-1
- **Temperature range**  
flexing -20°C to +80°C  
fixed installation -40°C to +80°C
- **Nominal voltage** U<sub>0</sub>/U 300/500 V
- **Test voltage** 3000 V
- **Insulation resistance**  
min. 20 MOhm x km
- **Coupling resistance**  
max. 250 Ohm/km
- **Minimum bending radius**  
flexing 20x cable Ø  
fixed installation 6x cable Ø
- **Radiation resistance**  
up to 100x10<sup>6</sup>cJ/kg (up to 100 Mrad)

## Cable structure

- Bare copper-conductor, to DIN VDE 0295 cl.5, fine-wire, BS 6360 cl.5, IEC 60228 cl.5
- Core insulation of special polymer
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay-length
- Special inner sheath
- Tinned copper braided screen, approx. 85% coverage
- Core wrapping of fleece guarantees easy cable stripping
- Outer sheath of special polymer compound
- Sheath colour dark green
- with meter marking

## Properties

- **Resistant to**  
Bio-fuel (diesel and petrol), highly resistant to biologically decomposable oils, Oxygene, Ozone, Hydrolysis and Microbes
- Low adhesion

## Note

- G = with green-yellow conductor  
x = without green-yellow conductor (OZ)
- <sup>1)</sup> For the critical applications we advise for consultation.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm<sup>2</sup>.
- unscreened analogue type: **BIOFLEX-500®-JZ**, confer page 109

## Application

HELUKABEL® BIOFLEX-500®-JZ-C is an extremely robust control cable with high abrasion and tear resistant properties. Due to its high resistance to Bio-fuel, Bio-oil and coolant emulsions. It is especially suited for use in the machine, tool making and plant industries as well as in the steel industry for difficult and problem areas. The inner sheaths of those cables raise the mechanical stress. The high flexibility of this cable type makes it quick and easy to install. Suitable for outdoor lying. These screened cables are particularly suitable for the interference-free transmission in instrumentation and control engineering applications (electromagnetic compatibility). <sup>1)</sup> For the critical applications we advise for consultation.

**EMC** = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
25691	2 x 0,5	6,6	41,0	68,0	20
25692	3 G 0,5	7,1	45,0	84,0	20
25693	4 G 0,5	7,6	54,0	95,0	20
25694	5 G 0,5	8,2	66,0	107,0	20
25695	7 G 0,5	9,4	79,0	135,0	20
25696	10 G 0,5	11,2	107,0	170,0	20
25697	12 G 0,5	11,3	137,0	195,0	20
25698	14 G 0,5	11,9	142,0	222,0	20
25699	18 G 0,5	12,9	156,0	278,0	20
25700	25 G 0,5	15,9	250,0	406,0	20
25701	2 x 0,75	7,2	46,0	88,0	19
25702	3 G 0,75	7,7	57,0	98,0	19
25703	4 G 0,75	8,2	63,0	112,0	19
25704	5 G 0,75	8,8	76,0	130,0	19
25705	7 G 0,75	10,1	100,0	185,0	19
25706	10 G 0,75	12,2	140,0	270,0	19
25707	12 G 0,75	12,3	175,0	294,0	19
25708	14 G 0,75	13,0	190,0	317,0	19
25709	18 G 0,75	14,6	240,0	357,0	19
25710	25 G 0,75	17,8	306,0	510,0	19
25711	41 G 0,75	21,5	403,0	951,0	19
25712	42 G 0,75	22,0	410,0	975,0	19

Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
25713	2 x 1	8,1	54,0	98,0	18
25714	3 G 1	8,5	64,0	102,0	18
25715	4 G 1	9,0	76,0	145,0	18
25716	5 G 1	9,9	89,0	170,0	18
25717	7 G 1	11,6	114,0	220,0	18
25718	10 G 1	14,0	156,0	330,0	18
25719	12 G 1	14,4	186,0	350,0	18
25720	14 G 1	15,0	198,0	402,0	18
25721	18 G 1	17,0	284,0	515,0	18
25722	25 G 1	20,6	387,0	690,0	18
25723	41 G 1	25,0	578,0	1070,0	18
25724	42 G 1	25,5	590,0	1096,0	18
25725	2 x 1,5	8,5	64,0	130,0	16
25726	3 G 1,5	8,9	82,0	152,0	16
25727	4 G 1,5	9,7	99,0	167,0	16
25728	5 G 1,5	10,8	123,0	203,0	16
25729	7 G 1,5	12,5	148,0	305,0	16
25730	10 G 1,5	15,1	198,0	422,0	16
25731	12 G 1,5	15,5	274,0	435,0	16
25732	14 G 1,5	16,1	294,0	480,0	16
25733	18 G 1,5	18,6	386,0	642,0	16
25734	25 G 1,5	22,1	531,0	803,0	16

Continuation ▶

# BIOFLEX-500®-JZ-C Bio-fuel resistant, abrasion resistant, recyclable environment friendly, bio-oil resistant<sup>1)</sup>, Cu-screened, EMC-preferred type, meter marking

A

Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No.cores x cross-sec. mm <sup>2</sup>	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
25735	41 G 1,5	27,2	840,0	1360,0	16	25748	4 G 6	17,0	316,0	560,0	10
25736	42 G 1,5	27,5	890,0	1375,0	16	25749	5 G 6	18,6	442,0	700,0	10
25737	2 x 2,5	10,6	110,0	180,0	14	25750	3 G 10	19,5	367,0	750,0	8
25738	3 G 2,5	11,1	148,0	215,0	14	25751	4 G 10	21,5	549,0	1023,0	8
25739	4 G 2,5	12,1	169,0	268,0	14	25752	5 G 10	23,9	604,0	1114,0	8
25740	5 G 2,5	13,2	220,0	349,0	14	25753	4 G 16	24,6	807,0	1385,0	6
25741	7 G 2,5	15,9	284,0	406,0	14	25754	5 G 16	27,3	940,0	1550,0	6
25742	12 G 2,5	19,5	470,0	720,0	14	25755	4 G 25	30,6	1169,0	1894,0	4
25743	2 x 4	12,6	124,0	300,0	12	25756	4 G 35	36,9	1680,0	2395,0	2
25744	3 G 4	13,4	178,0	340,0	12	25757	4 G 50	41,3	2370,0	3312,0	1
25745	4 G 4	15,0	234,0	408,0	12	25758	4 G 70	48,8	3257,0	4605,0	2/0
25746	5 G 4	16,4	284,0	504,0	12	25759	4 G 95	61,8	4060,0	6055,0	3/0
25747	3 G 6	15,2	245,0	453,0	10	25760	4 G 120	65,7	5231,0	7318,0	4/0

Dimensions and specifications may be changed without prior notice. (RA05)